

**ITEM C686.820031      MAST ARM TRAFFIC SIGNAL POLE COMBINATION ANCHOR  
BASE (30')**

**DESCRIPTION**

Under this item the CONTRACTOR shall furnish steel traffic signal poles as shown on the plans and as ordered by the ENGINEER.

**MATERIAL**

The steel poles herein specified are to be used for suspending traffic signal heads and luminaires.

Poles shall be the anchor base type and shall be either round or multisided, continuously tapered construction 0.14" per foot of length. The pole shall have a steel base electrically welded to the butt end of the pole. The anchor base shall telescope the butt end of the pole shaft and shall be continuously welded on the inside bottom and outside top. The pole shall be 30' in length "3" gauge steel with a butt diameter of 11" and a bolt circle of 15" and have a minimum yield of 55,000 psi in accordance with the latest ASTM specification.

The entire structure shall be hot dip galvanized in accordance with ASTM A123. The pole shall be one piece having no transverse joints or welds and no more than one longitudinal seam which shall be continuously welded and ground or rolled flush. Pole shall be of uniform cross section. The pole diameter shall be uniform at any cross section and the pole shall be straight. The poles shall be furnished with galvanized cast iron or aluminum removable pole caps and anchor bolt covers. Anchor bolt covers shall be attached to the base and pole by hex head bolts.

Galvanizing shall be in accordance with ASTM A123 specifications. Poles shall be furnished with a cast aluminum 3/8" dia. "J" hook bolted, or a 3/8" dia. galvanized steel "J" hook welded, inside the top of the pole and at an elevation 6" above the point of attachment of the mast arms. A grounding nut having 1/2" #13 tapped hole shall be located on the inside of the shaft above the handhole. The poles shall have a 4" x 8" reinforced handhole frame and removable cover located 12" to 15" from the butt end of the pole. Pole shall be furnished with four 1 3/4" x 90", 60,000 psi anchor bolts. Each anchor bolt shall be threaded 6" minimum on the top end and supplied with galvanized hexagon nuts and washers and lock nuts for this end. Anchor bolts shall be threaded 6" minimum at the base end and be provided with a 4" x 4" x 1" SQ steel nut for this end. The top 12" of the anchor bolts shall be hot dip galvanized. The pole shall be supplied with 2 brackets placed at right angles for attaching mast arms and at the elevation as shown on the plans. The bracket shall be continuously welded to the pole through the use of gusset plates, and shall be tapped to receive 1 1/4" high strength bolts in accordance with ASTM A325 as shown on the plans. The bracket shall be as shown on the plans. The pole shall be fitted with a simplex fitting (2 bolt type) as shown on the plans or as directed by the ENGINEER. All welding shall be in accordance with the NYS Steel Construction Manual. All material shall be in conformance with NYSDOT Standard Specifications, Section 724-03 Material Requirements Section A, latest revision..

**BASIS OF ACCEPTANCE**

**ITEM C686.820031      MAST ARM TRAFFIC SIGNAL POLE COMBINATION ANCHOR  
BASE (30')**

Acceptance of poles covered by this specification will be based on manufacturer's certification of compliance with the specification requirements signed by an officer of the company. Detailed drawings of the poles shall be submitted with the certifications.

**CONSTRUCTION DETAILS**

Poles shall be as specified on the Plans, Standard Sheets and as directed by the ENGINEER. Pole shall include attachment of fittings as specified on the Plans and Standard Sheets as follows:

- a.      Anchor bolt covers
- b.      Weatherheads and couplings, as required
- c.      Wire entrance
- d.      Pole cap

**METHOD OF MEASUREMENT**

Poles will be measured for payment as the number of each unit furnished in accordance with the contract documents or as directed by the ENGINEER.

**BASIS OF PAYMENT**

The unit bid price for each pole shall include all the items specified in the construction details, anchor bolts, and any other items required.

Payment will be made under:

<b><u>Item No.</u></b>	<b><u>Item</u></b>	<b><u>Pay Unit</u></b>
C686.820031	Mast Arm Traffic Signal Pole Combination Anchor Base (30')	Each