## **DESCRIPTION:**

Under this item the CONTRACTOR shall furnish and install shell with Z-crate visor. Shells are to be provided less glass, legend, lamp socket, etc., for installation of LED signal modules.

# **MATERIAL & CONSTRUCTION**

The signal shall consist of the following:

Dimensions and Weight

The maximum overall dimensions of the signal shall be 16" wide, 18" high, and 9" deep including the Z-crate type sun visor and hinges. The distance between the mounting surfaces of the upper (non-shurlock) and lower (shurlock) openings shall be 15-3/4". The weight of the signal, excluding mounting hardware, shall be 20 lbs. maximum.

Z Crate Visor - Refer to MCDOT Item C686.8108
CASE - Refer to MCDOT Item C686.8108
DOOR FRAME - Refer to MCDOT Item C686.8108
PAINTING - Refer to MCDOT Item C686.8108
ENVIRONMENTAL CONDITIONS - Refer to MCDOT Item C686.8108

### **OPTIONS-PAINT**

Standard Paint Housing Federal Yellow Paint Door Flat Black

### MOUNTING OPTIONS

Clamshell 2 mounting (pole left of message, or right of message). Contractor must determine which option is needed per the intersection drawing.

## **METHOD OF MEASUREMENT:**

The quantity to be paid for under this item will be the number of each unit installed in accordance with the plans and specifications.

## **BASIS OF PAYMENT:**

The unit bid price will be for each installation and shall include the cost of the furnishing all labor and equipment necessary to complete the work.

Payment will be made under:

Item No.	<u>Item</u>	Pay Unit
C686.8118	Clamshell Pedestrian Signal - Shell	Each

686-8118.doc 1 of 1 Last Revised 4-07