

**DESCRIPTION**

The work shall consist of rock excavation required for trenches, culverts, catch basins, manholes, conduit and direct burial cable in locations as shown on the plans and as directed by the ENGINEER.

The work shall conform to the requirements of NYSDOT Standard Specifications, Section 206, latest revision, with the following modifications:

**CONSTRUCTION DETAILS**

Rock Excavation in Trenches

Rock excavation in trenches consists of boulders, concrete and masonry exceeding 1/2 cubic yard in volume; and ledge rock which cannot, in the opinion of the ENGINEER, be removed without blasting or the use of pneumatic hammers. Concrete pavements and pavement foundations, and sanitary and storm sewers and their appurtenances will not be considered rock.

All blasting shall be done in accordance with all State and local laws, ordinances, and regulations relative to rock blasting. Attention is also directed to any requirements in the Contract Documents concerning blasting.

**METHOD OF MEASUREMENT**

Rock Excavation

Volumes of boulders, concrete, and masonry to be paid for under this item shall be as measured by the ENGINEER in the original position.

**BASIS OF PAYMENT**

Payment will be made under:

<b><u>Item No.</u></b>	<b><u>Item</u></b>	<b><u>Pay Unit</u></b>
C206.20	Trench and Culvert Rock Excavation	CY