

ITEM C555.02 SAND-CARVED DATE STAMP INSTALLATION

DESCRIPTION

The work shall consist of furnishing equipment and installing a sand-carved (blasted) date stamp applied to the surface of the concrete substructure in accordance with the Contract Plans, this specification and as directed by the Engineer.

MATERIALS

Sealer shall meet the requirements of the NYSDOT Standard Specifications, Section 717-03 Penetrating Type Protective Sealers, latest revision.

CONSTRUCTION DETAILS

The Sand-Carved Date Stamp shall be constructed in accordance with this specification, plans and the direction of the Engineer.

The concrete surface shall be dry and clean of any debris before installation of the date stamp. Concrete shall be removed by sand carving to a depth shown on the plans to achieve the proper relief. The date stamp shall leave a crisp, sharp definition in the concrete surface.

The concrete surface on the date stamp shall be treated with a Penetrating Type Protective Sealer after installation.

METHOD OF MEASUREMENT

Measurement will be for Each Sand-Carved Date Stamp that is installed where indicated on the Contract Plans.

BASIS OF PAYMENT

The unit price bid for each Sand-Carved Date Stamp shall include the cost of furnishing all labor, material, and equipment necessary to satisfactorily complete the work.

Payment will be made under:

<u>Item No.</u>	<u>Item</u>	<u>Pay Unit</u>
C555.02	Sand-Carved Date Stamp	Each